

## VPN Settings - Aggressive Mode

---

Connection Name	<input type="text" value="mkr2"/>
Local IPSec Identifier	<input type="text" value="mkr.local"/>
Remote IPSec Identifier	<input type="text" value="mkr.remote"/>
Tunnel can be accessed from	<input type="text" value="a subnet of local address"/>
Local LAN start IP Address	<input type="text" value="192"/> <input type="text" value="168"/> <input type="text" value="0"/> <input type="text" value="0"/>
Local LAN finish IP Address	<input type="text" value="0"/> <input type="text" value="0"/> <input type="text" value="0"/> <input type="text" value="0"/>
Local LAN IP Subnetmask	<input type="text" value="255"/> <input type="text" value="255"/> <input type="text" value="255"/> <input type="text" value="0"/>
Tunnel can access	<input type="text" value="all external addresses"/>
Remote LAN start IP Address	<input type="text" value="0"/> <input type="text" value="0"/> <input type="text" value="0"/> <input type="text" value="0"/>
Remote LAN finish IP Address	<input type="text" value="0"/> <input type="text" value="0"/> <input type="text" value="0"/> <input type="text" value="0"/>
Remote LAN IP Subnetmask	<input type="text" value="255"/> <input type="text" value="255"/> <input type="text" value="255"/> <input type="text" value="255"/>
Remote WAN IP or FQDN	<input type="text" value="0.0.0.0"/>

---

Secure Association	<input type="text" value="Aggressive Mode"/>
Perfect Forward Secrecy	<input checked="" type="radio"/> Enabled <input type="radio"/> Disabled
Encryption Protocol	<input type="text" value="3DES"/>
Key Group	<input type="text" value="Diffie-Hellman Group2"/>
PreShared Key	<input type="text" value="....."/>
Key Life	<input type="text" value="28800"/> Seconds
IKE Life Time	<input type="text" value="86400"/> Seconds
<input checked="" type="checkbox"/> NETBIOS Enable	

---

Apply

Cancel